



SAE Strike-Free Leverage Wrench 45° Offset Head

Hex Size	Part No.	Length in. a	Head Depth in. b	Head diameter in. c	Handle To Use	Weight lbs.
1"	66632	7½	7/8	2	24" Handle	2.5
1¼"	66634	7½	7/8	2	24" Handle	2.5
1½"	66636	7½	7/8	2	24" Handle	2.5
1¾"	66638	7½	7/8	2¼	24" Handle	2.5
2"	66640	7½	7/8	2¼	24" Handle	2.5
2¼"	66642	7½	7/8	2¼	24" Handle	2.5
2½"	66644	7½	7/8	2¼	24" Handle	2.5
2¾"	66646	8	1⅛	2¾	24" Handle	4.5
3"	66648	8	1⅛	2¾	24" Handle	4.5
3¼"	66650	8	1⅛	2¾	24" Handle	4.5
3½"	66652	8	1⅛	2¾	24" Handle	4.5
3¾"	66654	8	1⅛	2¾	36" Handle	4.5
4"	66656	8	1⅛	2¾	36" Handle	4.5
4¼"	66658	8	1⅛	2¾	36" Handle	4.5
4½"	66660	8	1⅛	2¾	36" Handle	4.5
4¾"	66662	8	1⅛	2¾	36" Handle	4.5
5"	66664	8¼	1⅛	3⅛	36" Handle	4.5
5¼"	66666	8¼	1⅛	3⅛	36" Handle	4.5
5½"	66668	8¼	1⅜	3⅝	36" Handle	7.0
5¾"	66670	9¼	1⅜	3¾	36" Handle	7.0
6"	66672	9¼	1⅜	3¾	36" Handle	7.0
6¼"	66674	9¼	1⅜	3¾	36" Handle	7.0
6½"	66676	9¼	1⅜	3¾	36" Handle	7.0
6¾"	66678	9½	1⅜	3¾	36" Handle	7.0
7"	66680	9½	1⅝	4	36" Handle	7.0
7¼"	66682	9½	1⅝	4⅛	36" Handle	7.0
7½"	66684	9½	1⅝	4⅛	36" Handle	7.0
7¾"	66686	10	1¾	4⅞	36" Handle	10.0
8"	66688	10	1¾	4⅞	36" Handle	10.0
8¼"	66690	10	1¾	4⅞	36" Handle	10.0
8½"	66692	10	1¾	4⅞	36" Handle	10.0
8¾"	66694	10	1¾	4⅞	36" Handle	10.0
9"	66696	10	1¾	4⅞	36" Handle	10.0
9¼"	66698	10	1¾	4⅞	36" Handle	10.0
9½"	66699	10	1¾	4⅞	36" Handle	10.0

FEATURES

- Engineered for optimum safety
- Increased leverage capability
- Dual purpose
- Interchangeable handle uniquely designed to fit competitor's model
- Widest range of sizes
- Ease of assembly

